

SATIN OIL

Maintenance Oil

Kährs Satin Oil is a hardening urethane oil for maintaining wood and parquet floors. Satin Oil gives the floor a protective oil layer with a beautiful shine. In order to minimize fumes, solvents used are Aliphatic naphtha.

Application

The surface to be maintained must be dry and free of dust and dirt.

1. Clean the floor with Kährs Cleaner. Use a cloth wetted with water and squeezed dry. Do not pour water onto the floor. Let the floor dry.
2. Machine Application – Normal Maintenance
Apply the oil on the surface. Preferable pour the needed amount of oil in a standard Spray bottle and spray the oil on the surface. Buff the floor with a cloth applied on a disk pad.

Machine Application – Cleaning of dirty floors

Apply the oil on the surface and spread out evenly and plentifully using a Yarn Mop. Buff the floor with a brown disk pad. Remove any excess oil using a rubber squeegee or cloth. Buff the floor with a cloth applied on a disk pad to remove any excess oil. Repeat the last step if needed.

Mop Application – Normal Maintenance

Apply the Oil with a clean cloth or preferably Kährs original mop. **Use a very small amount of oil at the time.** Preferable pour the needed amount of oil in a standard Spray bottle and spray the oil on the surface. Try and apply the oil when you have low incoming light on the floor. Work the mop/cloth lengthways along boards on the floor. Work methodically and cover the whole floor.

3. Allow floor to dry for at least 12 hours. Do not use the floor during this period. Allow the floor to dry for at least 7 days before replacing rugs etc.

Note! A danger of self-ignition exists in contact with organic materials (e.g. cotton cloths, saw dust, absorbing insulation materials etc.) due to self-drying oil content. Rags and other organic materials soaked in oil have to be put into water immediately after use, in order to avoid self-ignition.

Maintenance Intervals

Commercial use

Normal wear: 2-3 times/year
(first use in connection with floor installation)

Heavy wear: 4-6 times/year
(first use in connection with floor installation)

Residential use

As required
(first use in connection with floor installation)

Health and Environment

Kährs Satin Oil contains Aliphatic naphtha. Inhaling or frequent exposure may be hazardous. Avoid inhaling fumes. Usual precautions for handling chemical products should be observed. Ensure adequate ventilation. Use protective goggles and gloves. In case of ingestion, immediately seek medical advice and refer to container and label. For further information, please see the Material Safety Data Sheet.



Kährs

Article number: 710553

TECHNICAL DATA

Bonding agent:	Urethane modified alkyd resin
Solvent:	N-Paraffins
Solids by weight:	Approx. 22%
Coverage:	<u>Normal Maintenance</u> Approx. 1,5-3 dl/100 m ² <u>Cleaning of dirty floors</u> Approx. 1 l/15-20 m ²
Application temperature:	14-28 °C
Drying time	No wear for 12 hours
Shelf life:	24 months in unopened container. Do not expose to temperatures exceeding 40° C.
Frost tolerance:	Yes
Clean-up:	Use mineral spirits to clean tools before oil has hardened.
Toxicity:	Not classified
Flammability:	Not classified
Packaging:	0,75 liter steel can